




# Industrial Specification Grade Plugs and Connectors

2 Pole, 3 Wire Grounding  
 3 Pole, 3 Wire Non-Grounding  
 NEMA 5-15, 15A 125V  
 NEMA 6-15, 15A 250V,  
 NEMA 5-20, 20A 125V  
 NEMA 6-20, 20A 250V  
 Non-NEMA 15/10A, 125/250V

INDUSTRIAL  
 COMMERCIAL  
 RESIDENTIAL


## I-9 STRAIGHT BLADE PLUGS AND CONNECTORS



5666Y



5669Y



4472

### TESTING & CODE COMPLIANCE

- Listed to UL 498 (file no. E146159).
- UL verified to Federal Spec. WC-596
- CSA certified to C22.2 no. 42, (file no. LR1765). (4475 and 4472 are not UL or CSA listed).

### MATERIAL CHARACTERISTICS

Temperature Rating:  
 -40°C to 75°C.

### QuickGrip™ Dead-Front Plugs and Connectors

#### FEATURES

- One piece design and quick drive screws for fast wiring.
- High visibility yellow nylon for chemical and impact resistance.
- Combination head screws: Phillips/Robertson/slotted.
- UL verified to Federal Spec. WC-596F, CSA certified.

#### QuickGrip™ Dead-Front Plugs and Connectors

Rating A	V/AC	NEMA	Description	Cord Diameter	Color	Catalog No.	
						Plug	Connector
15	125	5-15	Straight	0.230-0.720" (5.8-18.3mm)	Yellow	5965Y	5969Y
			Straight	0.230-0.720" (5.8-18.3mm)	Black	5965BK	5969BK
15	250	6-15	Straight	0.230-0.720" (5.8-18.3mm)	Yellow	5666Y	5669Y
20	125	5-20	Straight	0.230-0.720" (5.8-18.3mm)	Yellow	5364Y	5369Y
20	250	6-20	Straight	0.230-0.720" (5.8-18.3mm)	Yellow	5464Y	5469Y

#### Rubber Dead-Front Plugs

Rating A	V/AC	NEMA	Description	Cord Diameter	Color	Catalog No.	
						Plug	Connector
15/10	125/250	Non-NEMA	Straight	0.560-.0650" (14.2-16.5mm)	Black	4475**	
				0.325-0.560" (8.3-14.2mm)	Black		4472**

\*\* Not Fed. Specs.

